

PERFORMANCE DATA SHEET FOR BRITA® SYSTEM WITH BRITA ELITE™ FILTER
(MODEL #OB06)

For System Model Numbers OB01, OB11, OB21, OB24, OB32, OB36, OB41, OB43, OB44, OB46, OB47, OB48, OB50, OB51, OB53, and OB60, and OB62 and Replacement Filter Model OB06.

IMPORTANT NOTICE: Read this Performance Data Sheet and compare the capabilities of this unit with your actual water treatment needs. It is recommended that, before purchasing a water treatment unit, you have your water supply tested to determine your actual water treatment needs.

These systems have been tested according to NSF/ANSI 401 (for applicable systems), 42 and 53 for reduction of the substances listed. The concentration of each of the indicated substances in water entering the systems was reduced to a concentration less than or equal to the permissible limit for water leaving the systems, as specified in NSF/ANSI 401, 42 and 53.

Substance	Brita Elite™ Reduction Data & NSF/ANSI Standard Requirements			
	Overall Percent Reduction	Influent Challenge Concentration	U.S. EPA Level/ NSF Maximum Permissible Product Water Concentration	Health Canada Guideline
NSF/ANSI Standard 42 – Health Effects				
Chlorine	97.4%	2.0±0.2 ppm	50%*	N/A
Particulate Reduction (Class I)	99.6%	>10000 particles/mL	85%*	N/A
NSF/ANSI Standard 53 – Health Effects				
Lead pH 6.5 [†]	99.5%	150±15 ppb	5 ppb	5 ppb
Lead pH 8.5 [†]	99.6%	150±15 ppb	5 ppb	5 ppb
Mercury pH 6.5	95.5%	6±0.6 ppb	2 ppb	1 ppb
Mercury pH 8.5	95.9%	6±0.6 ppb	2 ppb	1 ppb
Cadmium pH 6.5 [†]	96.9%	30±3 ppb	5 ppb	7 ppb
Cadmium pH 8.5 [†]	99.2%	30±3 ppb	5 ppb	7 ppb
Asbestos	>99%	55000000±45000000 Fibers/L	99%*	N/A
2,4-D	85.5%	210±21 ppb	70 ppb	100 ppb
Atrazine	99.3%	9±0.9 ppb	3 ppb	5 ppb
Benzene	93.5%	15±1.5 ppb	5 ppb	5 ppb
Endrin [†]	98.7%	6±0.6 ppb	2 ppb	N/A
Ethylbenzene	99.0%	2100±210 ppb	700 ppb	140 ppb
Carbon Tetrachloride [†]	91.2%	15±1.5 ppb	5 ppb	2 ppb
P-Dichlorobenzene	98.2%	225±23 ppb	75 ppb	5 ppb
Perfluorooctanoic Acid (PFOA) ^{^†} Perfluorooctane Sulfonate (PFOS) ^{^†}	98.1%	1.5 ± 0.15 ppb	0.07 ppb	0.2 ppb 0.6 ppb
Simazine	98.4%	12±4.8 ppb	4 ppb	10 ppb
Tetrachloroethylene	96.1%	15±4.5 ppb	5 ppb	10 ppb

Substance	Brita Elite™ Reduction Data & NSF/ANSI Standard Requirements			
	Overall Percent Reduction	Influent Challenge Concentration	U.S. EPA Level/NSF Maximum Permissible Product Water Concentration	Health Canada Guideline
NSF/ANSI Standard 401 – Emerging Compounds/Incidental Contaminants				
Atenolol†	>95%	200±40 ppt	30 ppt	N/A
Bisphenol A†	95.5%	2000±400 ppt	300 ppt	N/A
Carbamazepine†	>96%	1400±280 ppt	200 ppt	N/A
DEET†	98.0%	1400±280 ppt	200 ppt	N/A
Estrone†	96.4%	140±28 ppt	20 ppt	N/A
Ibuprofen†	94.9%	400±80 ppt	60 ppt	N/A
Linuron†	>93%	140±28 ppt	20 ppt	N/A
Meprobamate†	>94%	400±80 ppt	60 ppt	N/A
Metolachlor†	>94%	1400±280 ppt	200 ppt	50 ppb
Microplastics, particles 0.5-1 µm	99.6%	>10,000 particles/mL	85%*	N/A
Naproxen†	96.4%	140±28 ppt	20 ppt	N/A
Nonyl phenol†	93.5%	1400±280 ppt	200 ppt	N/A
Phenytoin†	>95%	200±40 ppt	30 ppt	N/A
TCEP†	99%	5000±1000 ppt	700 ppt	N/A
TCPP†	>99%	5000±1000 ppt	700 ppt	N/A
Trimethoprim†	>96%	140 ± 28 ppt	20 ppt	N/A

*NSF Minimum Percent Reduction Requirement

^Certified by IAPMO R&T.

‡Certified by NSF International

† Valid for the following systems: Slim/Metro (OB11), Ultramax Jet Black (OB24), Space Saver (OB21), Pacifica (OB41), Marina (OB47), Monterey (OB50), Wave (OB53), Everyday/Huron/Tahoe (OB60), and Denali (OB62).

Maintenance according to the manufacturer's instructions is essential for proper filter performance. Replace the Brita Elite™ pitcher filter (model# OB06) every 120 gallons/454 liters (about every 6 months for the average family). For maximum efficiency, process no more than 2 gallons/7.5 liters daily.

While testing was performed under standard laboratory conditions, actual performance may vary. The contaminants or other substances removed or reduced by this water treatment device are not necessarily in all users' water. Filter performance may vary based on local water conditions.

Brita Elite™ filter media contains silver to support the hygiene of the filter. A small amount of silver may be transferred to the water. This amount is well below the recommended maximum concentration set by the World Health Organization drinking water quality guidelines.

The Brita Elite™ pitcher filter is not intended to purify water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Individuals requiring water of special microbiological purity should follow the advice of their doctor or local health officials regarding the use and consumption of their tap water and Brita® filtered water.

The compounds certified under NSF/ANSI 401 have been deemed as “incidental contaminants/emerging compounds.” Incidental contaminants are those compounds that have been detected in drinking water supplies at trace levels. While occurring at only trace levels, these compounds can affect the public acceptance/perception of drinking water quality.

Hot water should not be used with the Brita Elite™ pitcher filter (Max. 29°C/85°F-Min. 0°C/32°F)

We offer a 30-day, unconditional, 100% money-back guarantee on all Brita® Pitchers, Faucet Filter Systems, Water Bottles and Filters. Call 1-800-24-BRITA (US) or 1-800-387-6940 (Canada).

Distributed in U.S.A. for: Brita LP, 1221 Broadway, Oakland, CA 94612

Distributed in Canada by: Brita Canada Corporation, 150 Biscayne Crescent, Brampton, ON L6W 4V3



The Brita Elite™ Filter (Model OB06) has been certified by IAPMO R&T against NSF/ANSI Standard 53 for the reduction of PFOA/PFOS in the Brita pitcher models specified on the Performance Data Sheet.



The Pacifica Pitcher (Model OB41) with Elite Filter (Model OB06) has been tested and certified by NSF International against NSF/ANSI Standard 53 for the reduction of lead.



The Brita Elite™ Filter (Model OB06) has been certified by WQA against NSF/ANSI Standards 42, 53, and 401 for the reduction of the claims in Brita system models specified on the Performance Data Sheet.